

RONTRON-Q-JUWEL

Range of flush-mounted control units and pilot lights for 22.3mm mounting dia. They are so flat (1.4 mm) to be used as a good alternative for membrane key-boards. The external shape of the front bezel underlines the flat design which combines elements of circle and square.

The mature detail design supports the formal originality of this product line. RONTRON-Q-JUWEL is a versatile modular system providing umpteen combination possibilities for many fields of application.

Degree of protection: IP65
Protection class: II



pushbuttons
with ring-shaped
illumination



pushbuttons
with
marking option



key switches



selector
switches



emergency stops



RONTRON-Q-JUWEL

The RONTRON-Q-JUWEL series fit the following contact units:

Standard contact block
Faston terminals 2.8 x 0.8 mm
Type series B...



Technical Data:

Acc. to VDE 0660 Ui~250V, Ith 6A
Acc. to VDE 0630
IEC/EN 61058
250V AC 6 (4) A
Lamp: 60V
Lamp socket: T5,5K/W2x4,6d
Lamp output: 1.2W max.



Electronic snap-action contact block
with soldering pins for PCB's
Type series CTP...



Rated voltage: 48V AC/DC (non-inductive)
Max. current: 0.1A
Min. current: 0.01mA
Lamp: 60V
Lamp socket: T5,5K
Lamp output: 1.2W max.



Electronic snap-action contact block
with up to two inverters
Faston terminals 2.8 x 0.8 mm
Type series CT...



Rated voltage: 48V AC/DC (non-inductive)
Max. current: 0.1A
Min. current: 0.01mA
Lamp: 60V
Lamp socket: T5,5K
Lamp output: 1.2W max.



with soldering connections for PCB's
Type series CZ...

Mounting depth dimensions

