

# RONTRON-R-JUWEL

Range of flush-mounted control units and pilot lights for 22.3mm mounting dia. They are so flat (1.4 mm) to be used as a good alternative for membrane key-boards. The external shape of the front bezel underlines the flat design. The mature detail design supports the formal originality of this product line. RONTRON-R-JUWEL is a versatile modular system providing umpteen combination possibilities for many fields of application.

Degree of protection: IP65

Protection class: II



pushbuttons  
with ring-shaped  
illumination

pushbuttons  
with  
marking option

key switches

selector switches

emergency stops



# RONTRON-R-JUWEL

The RONTRON-R-JUWEL series fit the following contact units:

Standard contact block  
Faston terminals 2.8 x 0.8 mm  
Type series B...



## Technical Data:

Acc.to VDE 0660 Ui~250V, Ith 6A  
Acc.to VDE 0630  
IEC/EN 61058  
250V AC 6 (4) A  
Lamp: 60V  
Lamp socket: T5,5K/W2x4,6d  
Lamp output: 1.2W max.



Electronic snap-action contact blocks  
with soldering connections for PCB's  
Type series CTP...



Rated voltage: 48V AC/DC (non-inductive)  
Max. current: 0.1A  
Min. current: 0.01mA  
Lamp: 60V  
Lamp socket: T5,5K  
Lamp output: 1.2W max.



Electronic snap-action contact blocks  
with up to two inverters  
Faston terminals 2.8 x 0.8 mm  
Type series CZ...  
with soldering connections for PCB's  
Type series CZ...



Rated voltage: 48V AC/DC (non-inductive)  
Max. current: 0.1A  
Min. current: 0.01mA  
Lamp: 60V  
Lamp socket: T5,5K  
Lamp output: 1.2W max.



## Mounting depth dimensions

